maharam

Application
Walls

Characteristics
Content: 65% Cellulose, 35% Latex
Finish: PFAS-Free Protective Topcoat
Backing: None
Reference Dimension: 10' H x 15' W (305cm x 457cm)
Traffic: Moderate Traffic
Customs: Repeatable, Scalable
Country of Origin: USA
Note: Colors depicted are not an exact representation of the final product. Please request a substrate sample for accurate quality and color reference.
Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls. Application must conform to current Installation Guidelines included in each shipment or available at maharam.com.

Price
Installation is sized, priced and produced on a project-specific basis.

Maintenance
W-Clean with water-based cleanser.

⊠ ⊠ ⊠ ⊠ Ⓦ

Testing
Flammability: AS/NZS 3837 Adhered
ASTM E84 Adhered
CAN ULC S102 Adhered
ISO 5660 Adhered

Lightfastness: AATCC 16.3, 40+ hours

✴ 🔥 🍃

maharam

Environmental
Greenguard Gold Certified
LBC Red List Free
Contains Bio-Based Content
FR Free
Free of Intentionally Added PFAS

Warranty
3 years.

Disclaimer
This artwork contains language or imagery that may not be suitable for all audiences.

© 2010 Harmen Liemburg, Maharam under license

Complete product information at maharam.com
800.645.3943

001